



Microdome Colour Camera

Product code: HDMICROD-330

This hi-resolution vandal-resistant camera fits neatly into vehicle roofs, and side walls. IP rating means it can be fitted internally and externally and is ideal for many types of vehicle installations such as cell vans, CIT, buses and ambulances. Alternative colours available.

Image Sensor/Resolution	1/3" 720P (AHD 1.0) Sony CMOS Sensor
Total Number of Pixels	All-pixel scan : 1312(H)*993(v)
Effective Pixels	
All-pixel scan	1312(H)*993(V)
HD720P	1280(H)*720(V)
Scanning System	2:1 Interlace
Video Output	AHD 1.0 / CVBS_1.2Vpp75(Ω) unbalanced
Gamma Characteristic	0.45 typ.
Performance	
Minimum Illumination (F1.2)	Colour: 0.1Lux(50IRE)/0.2Lux(15IRE)
Positioning	B/W: 00.1Lux/00.2Lux
DPC	LIVE&STATIC(White:2048,Black:128)

IR SMART	Software
WDR	DWDR
HLC	Software
MIR / V-MIR	Software
SHUTTER	AUTO (1/30 1/100,000)
DEFOG	Software
LENS SHADING	
DAY&NIGHT/SENS UP	COLOR / AUTO / BW / EXT
Camera ID	Off / on
White Balance	ATW/PUSH/USER1,2/MANUAL/PUSH LOCK
Privacy Mask	4 Area WINDOWS
DNR	OFF / 2D / 3D & Software
TDN	OPTION
Lens	BOARD LENS (ONLY)
Audio	BOARD IN (OPTION)
Sensitivity	0.1Lux @F1.4
S/N Ratio	More than 46dB
Power Supply	Regulated at DC 12.0V (7.5V 24V)
Power Consumption	85mA (at DC 12V) Max
Operation Temp.	-10 85°C
Dimension	32mm(W) x 32mm(H)
SENSOR	IMX225LQR-C